

## Technical specification sheet

# IPU-S32S25E-EC | Extremely Durable Pump

Specifications		
article number		101.002.639
model		IPU-S32S25E-EC
max. working pressure	psi	5076
for cutter type		stationary HSC200STH40
short description		Extremely Durable Pump
capacity oil tank (effective)	oz	845.4
number of stages		1
first stage output / min.	oz	108.2
first stage pressure range	psi	0 - 5076
operator type		electric motor
engine		400 VAC - 2.2 kW - 50 Hz - 3 Ph
speed	rpm	2850
weight, ready for use	lb	264.6
dimensions (AxBxC)	in	20.6 x 25.2 x 25.6

Technical drawing dimensions		
dimension A	in	20.6
dimension B	in	25.2
dimension C	in	25.6



[holmatro.com](http://holmatro.com)

© Holmatro 2025-11-05

While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.