

HBP05D02 | APEIRON Holmatro Battery Pump

Specifications		
article number		101.003.399
model		HBP05D02
max. working pressure	psi	10443
short description		APEIRON Holmatro Battery Pump
battery included		Yes, 2 pcs
connectivity, mobile app		Bluetooth
number of stages		stepless
high pressure output / min	oz	16.91
low pressure output / min	oz	104.82
capacity oil tank	oz	84.5
capacity oil tank (effective)	oz	67.6
protection rate		IP44
sound emission @ 1m/3.25ft	dB(A)	75
sound emission @ 4m/13ft	dB(A)	61
operator type		battery
acting type		double
couplers		yes, 2 pcs A119 male
hydraulic oil type		ISO-L HV VG 36
engine		28 VDC - 0.8 kW
weight, ready for use	lb	29.3
dimensions (LxWxH)	in	20.5 x 8.9 x 10.2
temperature range	°F	-4 +131
dimensions (AxBxC)	in	20.5 x 10.2 x 8.9
weight (excl. battery)	lb	25.8

Standard supplied with

- 2 Batteries
- Hand pendant control, 3m length cord
- Couplers that suit the application: plug and play

Required Accessories

Battery Charger PBCH1 (AC-EU)	101.003.242
Battery Charger PBCH5 (AC-UK)	101.003.243
Battery Charger PBCH2 (AC-US)	101.003.244

