Technical specification sheet

PA 04 H 2 | Aluminum Hand Pump

Specifications		
article number		100.142.033
short description		Aluminum Hand Pump
model		PA 04 H 2
max. working pressure	bar/MPa	720 / 72
capacity oil tank (effective)	cc	400
capacity oil tank	cc	500
number of stages		2
first stage output (per stroke)	cc	18.4
second stage output (per stroke)	cc	1.4
first stage pressure range	bar/MPa	0 - 45 / 0 - 4.5
second stage pressure range	bar/MPa	45 - 720 / 4.5 - 72
max. operating force	kg	32.0
connection		3/8” NPT female
operator type		hand
double acting optional		no
weight, ready for use	kg	3.4

Technical drawing dimensions		
dimension A	mm	434
dimension B	mm	135
dimension C	mm	165



holmatro.com

© Holmatro 2026-09-29
While the greatest care has been devoted to the content, it is possible that the information in this printed matter is incorrect or incomplete. Holmatro B.V. and its affiliated companies (hereafter: Holmatro) cannot be held liable in any way for the consequences of activities undertaken on the basis of this printed matter. Values can vary within the manufacturer measurements. If you have any doubts about the correctness or completeness of the information, you shall contact Holmatro (T +31 (0)162-751480). Nothing from this printed matter can be copied and/or made public in any way without the explicit authorisation of Holmatro.